



O-RINGS, INC.
 3311 PEPPER AVENUE
 LOS ANGELES, CA 90065
 PHONE (323) 343-9500
 FAX (323) 343-9505
 sales@oringsUSA.com

O-RINGS – JIS2401 Sizes (P Series)

Size	ID		C/S (W)		ID		C/S (W)		Size
	mm	±	mm		in	±	in	±	
P-3	2.8	0.12	1.9		0.11	0.005	0.075	0.003	P-3
P-4	3.8	0.12	1.9		0.15	0.005	0.075	0.003	P-4
P-5	4.8	0.12	1.9		0.189	0.005	0.075	0.003	P-5
P-6	5.8	0.12	1.9		0.228	0.005	0.075	0.003	P-6
P-7	6.8	0.12	1.9		0.268	0.005	0.075	0.003	P-7
P-8	7.8	0.12	1.9		0.307	0.005	0.075	0.003	P-8
P-9	8.8	0.12	1.9		0.346	0.005	0.075	0.003	P-9
P-10	9.8	0.12	1.9		0.386	0.005	0.075	0.003	P-10
P-10A	9.8	0.12	2.4		0.386	0.005	0.094	0.003	P-10A
P-11	10.8	0.12	2.4		0.425	0.005	0.094	0.003	P-11
P-11.2	11	0.12	2.4		0.433	0.005	0.094	0.003	P-11.2
P-12	11.8	0.12	2.4		0.465	0.005	0.094	0.003	P-12
P-12.5	12.3	0.12	2.4		0.484	0.005	0.094	0.003	P-12.5
P-14	13.8	0.12	2.4		0.543	0.005	0.094	0.003	P-14
P-15	14.8	0.12	2.4		0.583	0.005	0.094	0.003	P-15
P-16	15.8	0.12	2.4		0.622	0.005	0.094	0.003	P-16
P-18	17.8	0.12	2.4		0.701	0.005	0.094	0.003	P-18
P-20	19.8	0.15	2.4		0.78	0.006	0.094	0.003	P-20
P-21	20.8	0.15	2.4		0.819	0.006	0.094	0.003	P-21
P-22	21.8	0.15	2.4		0.858	0.006	0.094	0.003	P-22
P-22A	21.7	0.15	3.5		0.854	0.006	0.138	0.004	P-22A
P-22.4	22.1	0.15	3.5		0.87	0.006	0.138	0.004	P-22.4
P-24	23.7	0.15	3.5		0.933	0.006	0.138	0.004	P-24
P-25	24.7	0.15	3.5		0.972	0.006	0.138	0.004	P-25
P-25.5	25.2	0.15	3.5		0.992	0.006	0.138	0.004	P-25.5
P-26	25.7	0.15	3.5		1.012	0.006	0.138	0.004	P-26
P-28	27.7	0.15	3.5		1.091	0.006	0.138	0.004	P-28
P-29	28.7	0.15	3.5		1.13	0.006	0.138	0.004	P-29
P-29.5	29.2	0.15	3.5		1.15	0.006	0.138	0.004	P-29.5
P-30	29.7	0.15	3.5		1.169	0.006	0.138	0.004	P-30
P-31	30.7	0.15	3.5		1.209	0.006	0.138	0.004	P-31
P-31.5	31.2	0.15	3.5		1.228	0.006	0.138	0.004	P-31.5
P-32	31.7	0.15	3.5		1.248	0.006	0.138	0.004	P-32
P-34	33.7	0.15	3.5		1.327	0.006	0.138	0.004	P-34
P-35	34.7	0.15	3.5		1.366	0.006	0.138	0.004	P-35
P-35.5	35.2	0.15	3.5		1.386	0.006	0.138	0.004	P-35.5
P-36	35.7	0.15	3.5		1.406	0.006	0.138	0.004	P-36
P-38	37.7	0.15	3.5		1.484	0.006	0.138	0.004	P-38
P-39	38.7	0.15	3.5		1.524	0.006	0.138	0.004	P-39
P-40	39.7	0.15	3.5		1.563	0.006	0.138	0.004	P-40
P-41	40.7	0.25	3.5		1.602	0.01	0.138	0.004	P-41
P-42	41.7	0.25	3.5		1.642	0.01	0.138	0.004	P-42
P-44	43.7	0.25	3.5		1.72	0.01	0.138	0.004	P-44
P-45	44.7	0.25	3.5		1.76	0.01	0.138	0.004	P-45
P-46	45.7	0.25	3.5		1.799	0.01	0.138	0.004	P-46



O-RINGS, INC.
3311 PEPPER AVENUE
LOS ANGELES, CA 90065
PHONE (323) 343-9500
FAX (323) 343-9505
sales@oringsUSA.com

O-RINGS – JIS2401 Sizes (P Series)

Size	ID		C/S (W)		ID		C/S (W)		Size
	mm	±	mm		in	±	in	±	
P-48	47.7	0.25	3.5		1.878	0.01	0.138	0.004	P-48
P-49	48.7	0.25	3.5		1.917	0.01	0.138	0.004	P-49
P-50	49.7	0.25	3.5		1.957	0.01	0.138	0.004	P-50
P-48A	47.6	0.25	5.7		1.874	0.01	0.224	0.006	P-48A
P-50A	49.6	0.25	5.7		1.953	0.01	0.224	0.006	P-50A
P-52	51.6	0.25	5.7		2.031	0.01	0.224	0.006	P-52
P-53	52.6	0.25	5.7		2.071	0.01	0.224	0.006	P-53
P-55	54.6	0.25	5.7		2.15	0.01	0.224	0.006	P-55
P-56	55.6	0.25	5.7		2.189	0.01	0.224	0.006	P-56
P-58	57.6	0.25	5.7		2.268	0.01	0.224	0.006	P-58
P-60	59.6	0.25	5.7		2.346	0.01	0.224	0.006	P-60
P-62	61.6	0.25	5.7		2.425	0.01	0.224	0.006	P-62
P-63	62.6	0.25	5.7		2.465	0.01	0.224	0.006	P-63
P-65	64.6	0.25	5.7		2.543	0.01	0.224	0.006	P-65
P-67	66.6	0.25	5.7		2.622	0.01	0.224	0.006	P-67
P-70	69.6	0.25	5.7		2.74	0.01	0.224	0.006	P-70
P-71	70.6	0.4	5.7		2.78	0.016	0.224	0.006	P-71
P-75	74.6	0.4	5.7		2.937	0.016	0.224	0.006	P-75
P-80	79.6	0.4	5.7		3.134	0.016	0.224	0.006	P-80
P-85	84.6	0.4	5.7		3.331	0.016	0.224	0.006	P-85
P-90	89.6	0.4	5.7		3.528	0.016	0.224	0.006	P-90
P-95	94.6	0.4	5.7		3.724	0.016	0.224	0.006	P-95
P-100	99.6	0.4	5.7		3.921	0.016	0.224	0.006	P-100
P-102	101.6	0.4	5.7		4	0.016	0.224	0.006	P-102
P-105	104.6	0.4	5.7		4.118	0.016	0.224	0.006	P-105
P-110	109.6	0.4	5.7		4.315	0.016	0.224	0.006	P-110
P-112	111.6	0.4	5.7		4.394	0.016	0.224	0.006	P-112
P-115	114.6	0.4	5.7		4.512	0.016	0.224	0.006	P-115
P-120	119.6	0.4	5.7		4.709	0.016	0.224	0.006	P-120
P-125	124.6	0.4	5.7		4.906	0.016	0.224	0.006	P-125
P-130	129.6	0.6	5.7		5.102	0.024	0.224	0.006	P-130
P-132	131.6	0.6	5.7		5.181	0.024	0.224	0.006	P-132
P-135	134.6	0.6	5.7		5.299	0.024	0.224	0.006	P-135
P-140	139.6	0.6	5.7		5.496	0.024	0.224	0.006	P-140
P-145	144.6	0.6	5.7		5.693	0.024	0.224	0.006	P-145
P-150	149.6	0.6	5.7		5.89	0.024	0.224	0.006	P-150
P-150A	149.5	0.6	8.4		5.886	0.024	0.331	0.006	P-150A
P-155	154.5	0.6	8.4		6.083	0.024	0.331	0.006	P-155
P-160	159.5	0.6	8.4		6.28	0.024	0.331	0.006	P-160
P-165	164.5	0.6	8.4		6.476	0.024	0.331	0.006	P-165
P-170	169.5	0.6	8.4		6.673	0.024	0.331	0.006	P-170
P-175	174.5	0.6	8.4		6.87	0.024	0.331	0.006	P-175
P-180	179.5	0.6	8.4		7.067	0.024	0.331	0.006	P-180
P-185	184.5	0.8	8.4		7.264	0.031	0.331	0.006	P-185
P-190	189.5	0.8	8.4		7.461	0.031	0.331	0.006	P-190



O-RINGS, INC.
3311 PEPPER AVENUE
LOS ANGELES, CA 90065
PHONE (323) 343-9500
FAX (323) 343-9505
sales@oringsUSA.com

O-RINGS – JIS2401 Sizes (P Series)

Size	ID		C/S (W)		ID		C/S (W)		Size
	mm	±	mm		in	±	in	±	
P-195	194.5	0.8	8.4		7.657	0.031	0.331	0.006	P-195
P-200	199.5	0.8	8.4		7.854	0.031	0.331	0.006	P-200
P-205	204.5	0.8	8.4		8.051	0.031	0.331	0.006	P-205
P-209	208.5	0.8	8.4		8.209	0.031	0.331	0.006	P-209
P-210	209.5	0.8	8.4		8.248	0.031	0.331	0.006	P-210
P-215	214.5	0.8	8.4		8.445	0.031	0.331	0.006	P-215
P-220	219.5	0.8	8.4		8.642	0.031	0.331	0.006	P-220
P-225	224.5	0.8	8.4		8.839	0.031	0.331	0.006	P-225
P-230	229.5	0.8	8.4		9.035	0.031	0.331	0.006	P-230
P-235	234.5	0.8	8.4		9.232	0.031	0.331	0.006	P-235
P-240	239.5	0.8	8.4		9.429	0.031	0.331	0.006	P-240
P-245	244.5	0.8	8.4		9.626	0.031	0.331	0.006	P-245
P-250	249.5	0.8	8.4		9.823	0.031	0.331	0.006	P-250
P-255	254.5	0.8	8.4		10.02	0.031	0.331	0.006	P-255
P-260	259.5	0.8	8.4		10.217	0.031	0.331	0.006	P-260
P-265	264.5	0.8	8.4		10.413	0.031	0.331	0.006	P-265
P-270	269.5	0.8	8.4		10.61	0.031	0.331	0.006	P-270
P-275	274.5	0.8	8.4		10.807	0.031	0.331	0.006	P-275
P-280	279.5	0.8	8.4		11.004	0.031	0.331	0.006	P-280
P-285	284.5	0.8	8.4		11.201	0.031	0.331	0.006	P-285
P-290	289.5	0.8	8.4		11.398	0.031	0.331	0.006	P-290
P-295	294.5	0.8	8.4		11.594	0.031	0.331	0.006	P-295
P-300	299.5	0.8	8.4		11.791	0.031	0.331	0.006	P-300
P-315	314.5	1	8.4		12.382	0.039	0.331	0.006	P-315
P-320	319.5	1	8.4		12.579	0.039	0.331	0.006	P-320
P-335	334.5	1	8.4		13.169	0.039	0.331	0.006	P-335
P-340	339.5	1	8.4		13.366	0.039	0.331	0.006	P-340
P-355	354.5	1	8.4		13.957	0.039	0.331	0.006	P-355
P-360	359.5	1	8.4		14.154	0.039	0.331	0.006	P-360
P-375	374.5	1	8.4		14.744	0.039	0.331	0.006	P-375
P-385	384.5	1	8.4		15.138	0.039	0.331	0.006	P-385
P-400	399.5	1	8.4		15.728	0.039	0.331	0.006	P-400
G-25	24.4	0.15	3.1		0.961	0.006	0.122	0.004	G-25
G-30	29.4	0.15	3.1		1.157	0.006	0.122	0.004	G-30
G-35	34.4	0.15	3.1		1.354	0.006	0.122	0.004	G-35
G-40	39.4	0.15	3.1		1.551	0.006	0.122	0.004	G-40
G-45	44.4	0.25	3.1		1.748	0.01	0.122	0.004	G-45
G-50	49.4	0.25	3.1		1.945	0.01	0.122	0.004	G-50
G-55	54.4	0.25	3.1		2.142	0.01	0.122	0.004	G-55
G-60	59.4	0.25	3.1		2.339	0.01	0.122	0.004	G-60
G-65	64.4	0.25	3.1		2.535	0.01	0.122	0.004	G-65
G-70	69.4	0.25	3.1		2.732	0.01	0.122	0.004	G-70
G-75	74.4	0.4	3.1		2.929	0.016	0.122	0.004	G-75
G-80	79.4	0.4	3.1		3.126	0.016	0.122	0.004	G-80
G-85	84.4	0.4	3.1		3.323	0.016	0.122	0.004	G-85



O-RINGS, INC.
3311 PEPPER AVENUE
LOS ANGELES, CA 90065
PHONE (323) 343-9500
FAX (323) 343-9505
sales@oringsUSA.com

O-RINGS – JIS2401 Sizes (P Series)

Size	ID		C/S (W)		ID		C/S (W)		Size
	mm	±	mm		in	±	in	±	
G-90	89.4	0.4	3.1		3.52	0.016	0.122	0.004	G-90
G-95	94.4	0.4	3.1		3.717	0.016	0.122	0.004	G-95
G-100	99.4	0.4	3.1		3.913	0.016	0.122	0.004	G-100
G-105	104.4	0.4	3.1		4.11	0.016	0.122	0.004	G-105
G-110	109.4	0.4	3.1		4.307	0.016	0.122	0.004	G-110
G-115	114.4	0.4	3.1		4.504	0.016	0.122	0.004	G-115
G-120	119.4	0.4	3.1		4.701	0.016	0.122	0.004	G-120
G-125	124.4	0.4	3.1		4.898	0.016	0.122	0.004	G-125
G-130	129.4	0.6	3.1		5.094	0.024	0.122	0.004	G-130
G-135	134.4	0.6	3.1		5.291	0.024	0.122	0.004	G-135
G-140	139.4	0.6	3.1		5.488	0.024	0.122	0.004	G-140
G-145	144.4	0.6	3.1		5.685	0.024	0.122	0.004	G-145
G-150	149.3	0.6	5.7		5.878	0.024	0.224	0.006	G-150
G-155	154.3	0.6	5.7		6.075	0.024	0.224	0.006	G-155
G-160	159.3	0.6	5.7		6.272	0.024	0.224	0.006	G-160
G-165	164.3	0.6	5.7		6.469	0.024	0.224	0.006	G-165
G-170	169.3	0.6	5.7		6.665	0.024	0.224	0.006	G-170
G-175	174.3	0.6	5.7		6.862	0.024	0.224	0.006	G-175
G-180	179.3	0.6	5.7		7.059	0.024	0.224	0.006	G-180
G-185	184.3	0.8	5.7		7.256	0.031	0.224	0.006	G-185
G-190	189.3	0.8	5.7		7.453	0.031	0.224	0.006	G-190
G-195	194.3	0.8	5.7		7.65	0.031	0.224	0.006	G-195
G-200	199.3	0.8	5.7		7.846	0.031	0.224	0.006	G-200
G-210	209.3	0.8	5.7		8.24	0.031	0.224	0.006	G-210
G-220	219.3	0.8	5.7		8.634	0.031	0.224	0.006	G-220
G-230	229.3	0.8	5.7		9.028	0.031	0.224	0.006	G-230
G-240	239.3	0.8	5.7		9.421	0.031	0.224	0.006	G-240
G-250	249.3	0.8	5.7		9.815	0.031	0.224	0.006	G-250
G-255	254.3	0.8	5.7		10.012	0.031	0.224	0.006	G-255
G-260	259.3	0.8	5.7		10.209	0.031	0.224	0.006	G-260
G-270	269.3	0.8	5.7		10.602	0.031	0.224	0.006	G-270
G-280	279.3	0.8	5.7		10.996	0.031	0.224	0.006	G-280
G-290	289.3	0.8	5.7		11.39	0.031	0.224	0.006	G-290
G-300	299.3	0.8	5.7		11.783	0.031	0.224	0.006	G-300
V-15	14.5	0.15	4		0.571	0.006	0.157	0.004	V-15
V-24	23.5	0.15	4		0.925	0.006	0.157	0.004	V-24
V-34	33.5	0.15	4		1.319	0.006	0.157	0.004	V-34
V-40	39.5	0.15	4		1.555	0.006	0.157	0.004	V-40
V-55	54.5	0.25	4		2.146	0.01	0.157	0.004	V-55
V-70	69	0.25	4		2.717	0.01	0.157	0.004	V-70
V-85	84	0.4	4		3.307	0.016	0.157	0.004	V-85
V-100	99	0.4	4		3.898	0.016	0.157	0.004	V-100
V-120	119	0.4	4		4.685	0.016	0.157	0.004	V-120
V-150	148.5	0.6	4		5.846	0.024	0.157	0.004	V-150
V-175	173	0.6	4		6.811	0.024	0.157	0.004	V-175



O-RINGS, INC.
 3311 PEPPER AVENUE
 LOS ANGELES, CA 90065
 PHONE (323) 343-9500
 FAX (323) 343-9505
 sales@oringsUSA.com

O-RINGS – JIS2401 Sizes (P Series)

Size	ID		C/S (W)		ID		C/S (W)		Size
	mm	±	mm		in	±	in	±	
V-225	222.5	0.8	6		8.76	0.031	0.236	0.006	V-225
V-275	272	0.8	6		10.709	0.031	0.236	0.006	V-275
V-325	321.5	1	6		12.657	0.039	0.236	0.006	V-325
V-380	376	1	6		14.803	0.039	0.236	0.006	V-380
V-430	425.5	1.2	6		16.752	0.047	0.236	0.006	V-430
V-480	475	1.2	10		18.701	0.047	0.394	0.012	V-480
V-530	524.5	1.6	10		20.65	0.063	0.394	0.012	V-530
V-585	579	1.6	10		22.795	0.063	0.394	0.012	V-585
V-640	633.5	1.6	10		24.941	0.063	0.394	0.012	V-640
V-690	683	1.6	10		26.89	0.063	0.394	0.012	V-690
V-740	732.5	2	10		28.839	0.079	0.394	0.012	V-740
V-790	782	2	10		30.787	0.079	0.394	0.012	V-790
V-845	836.5	2	10		32.933	0.079	0.394	0.012	V-845
V-950	940.5	2.5	10		37.028	0.098	0.394	0.012	V-950
V-1055	1044	3	10		41.102	0.118	0.394	0.012	V-1055